



Crick, Northampton NN6 7XS
 01788 823811
 sales@access-irrigation.co.uk
 www.access-irrigation.co.uk



Approximate dimensions (unpacked) 110cm long x 63cm wide x 67cm high, weight 38kg

Operating off mains water pressure, this machine offers an excellent cost effective watering option.

The Speedy Rain 25/50 is the ideal solution for watering the following:

- Rugby/Football pitches
- Small scale sports turf
- Landscape/Amenity areas
- Large gardens
- Equestrian/Riding arenas

Features

- Reliable and cost effective irrigation
- Operates from mains water supply (from 2.2 bar)
- Low pressure piston drive
- Low maintenance drive mechanism
- Variable rewind speeds
- Part circle impact sprinkler and steel sled base (two-wheel trolley can be supplied in place of the sled at extra cost)

Specifications	
Hose diameter & length	25mm x 50m
Drive mechanism	Piston
Output range	0.7-2.7 m ³ /hr
Connection pressure (at machine)	1.5-5 bar
Throw diameter	18-28m
Maximum irrigation area per setting	0.35 acres
Rewind speed	5-40 meters per hour

Speedy Rain 25/50 Reel Irrigator

RM Speedy Rain 25/50

Nozzle mm	Pressure		Flow Capacity m ³ /hr	Throw Radius mtr	Throw Diameter mtr	Irrigated Strip 85%	Rewind Speed (metres/hour)								
	At Machine bar	At Sprinkler bar					5	10	15	20	25	30	40	50	
	Suggested							Rewinding Time In Hours							
							Approximate Water Application (mm)								
4	2.2	1.5	0.2	0.72	11	22	18.7	7.7	3.9	2.6	1.9	1.5	1.3	1.0	0.8
	2.8	2	0.23	0.84	12	24	20.4	8.2	4.1	2.7	2.1	1.6	1.4	1.0	0.8
**	3.9	3	0.28	1.02	13	26	22.1	9.2	4.6	3.1	2.3	1.8	1.5	1.2	0.9
5	2.5	1.5	0.33	1.2	12	24	20.4	11.8	5.9	3.9	2.9	2.4	2.0	1.5	1.2
	3.1	2	0.37	1.32	13	26	22.1	11.9	6.0	4.0	3.0	2.4	2.0	1.5	1.2
	4.4	3	0.45	1.62	14	28	23.8	13.6	6.8	4.5	3.4	2.7	2.3	1.7	1.4
6	2.9	1.5	0.47	1.68	13	26	22.1	15.2	7.6	5.1	3.8	3.0	2.5	1.9	1.5
	3.7	2	0.53	1.92	14	28	23.8	16.1	8.1	5.4	4.0	3.2	2.7	2.0	1.6
	5.1	3	0.65	2.34	15	30	25.5	18.4	9.2	6.1	4.6	3.7	3.1	2.3	1.8

** Standard Nozzle

** Amount of water exhausted from piston to complete each cycle = 329 litres