RESIDENTIAL & COMMERCIAL IRRIGATION
Built on Innovation®

01 | **Save time:** Manage from anywhere around the world

02 | **Save money:** Avoid costly on-site visits by making schedule changes from anywhere

03 | **Predictive Watering Adjustments:** Integrate local weather data to make water-saving scheduling adjustments

Hydrawise™ Ready

PRO-HC RESIDENTIAL OUTDOOR PROFESSIONAL-GRADE WI-FI CONTROLLER WITH HYDRAWISE™ WEB-BASED SOFTWARE

Manage your outdoor irrigation controller from anywhere worldwide using your smart device or web browser with Hydrawise cloud software. Predictive watering adjusts schedules based on temperature forecast, rainfall probability, and wind and humidity to provide maximum water savings while keeping your landscape healthy and beautiful. Add a simple-to-install flow meter and set up automatic notifications to alert you of broken pipes or sprinklers.

Hydrawise cloud software is a user-friendly water management software. Each homeowner can use predictive watering adjustments to achieve water savings. Hydrawise software enables professional contractors to do in-depth water management, and monitor the piping and electrical systems. It is a professional cloud-based irrigation software that works for everyone.

The Pro-HC Controller is Smart WaterMark approved when connected to the Hydrawise web-based software.

Smart Approved WaterMark

Try Hydrawise now.
Visit hydrawise.com

▍**Learn more.** Visit hunterindustries.com, or contact your local sales manager.

PRO-HC CONTROLLER FEATURES & SPECIFICATIONS

Features

- Full-functioning controller with touchscreen
- Wi-Fi enabled for simple and fast connection to the internet
- 6, 12 and 24 fixed station controllers
- Dedicated master valve/pump start
- Large terminal strips
- Built-in milliamp sensor
- 2 sensor ports
- Warranty: 2 years

Models

Plastic Indoor
Height: 21 cm
Width: 24 cm
Depth: 8.8 cm

Plastic Outdoor
Height: 22.8 cm
Width: 25 cm
Depth: 10 cm

HC Flow Meter - ¾" (20 mm) BSP thread
Height: 13 cm
Length: 8 cm
Depth: 8 cm

HC Flow Meter - 1" (25 mm) BSP thread
Height: 16 cm
Length: 8 cm
Depth: 8 cm

Advanced Features

- **Touchscreen Interface:** The Pro-HC controller has a full graphical touchscreen interface, which makes it easy to program and start manually.
- **Predictive Watering™ Adjustments:** Daily schedule adjustments (based on local weather data) monitor past, current, and forecasted temperature, rainfall, humidity, and wind speed. This allows for adjustments of watering times and schedules to balance water savings with water efficiency for plants.
- **Flow Meter Detection And Alerts:** Monitor the state of the piping system with an optional flow meter. Receive automatic alerts when a pipe is broken to prevent property damage.
- **Wiring Detection and Alerts:** The Pro-HC controller continuously monitors the electrical current flowing to solenoid valves. If the current is too high or too low, Hydrawise will alert you and tell you which valve is not working properly. This allows you to fix a failed valve before damage is done to the landscape.
- **Advanced Sensor Ports:** Two general purpose sensor ports can be used for many different functions. Sensor ports work with Hunter HC flow meters, Hunter Clik and standard rain and soil sensors to stop irrigation. The sensor ports can also start an irrigation cycle. This allows you to create custom starts based on sensor readings.
- **Built to Last:** The Pro-HC features a double-door design, which makes it extremely durable in all weather conditions. It also includes large terminal strips for easy installation of solenoid wiring.

HC − SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Models	**2** Transformer	**3** Outdoor	**4** Options
PHC-6 = 6 station controller with Wi-Fi connection	**00** = 120 VAC	**(Blank)** = Outdoor model (internal transformer)	**(Blank)** = No option
PHC-12 = 12 station controller with Wi-Fi connection	**01** = 230 VAC		**E** = 230 VAC with European connections
PHC-24 = 24 station controller with Wi-Fi connection			**A** = 230 VAC with Australian connections

Examples: PHC-600i = 6-Station 120 VAC indoor plastic controller

HC − OPTIONS

Models	Description
HC-075-FLOW	Flow Meter w/ ¾" (20 mm) NPT thread
HC-100-FLOW	Flow Meter w/ 1" (25 mm) NPT thread
HC-075-FLOW-B	Flow Meter with 20 mm BSP thread
HC-100-FLOW-B	Flow Meter with 25 mm BSP thread

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

Gregory R. Hunter, President of Hunter Industries

FSC
www.fsc.org
MIX
Paper from responsible sources
FSC® C006076