# **ACCU SYNC®**

## **OPERATING SPECIFICATIONS**

- Regulation from 20 to 100 PSI
- Static pressure: 150 PSI
- Required dynamic pressure differential: 15 PSI
- Works with AC and DC latching solenoids
- Works with any Hunter valve



Type: Pressure Regulator

## ADAPTER





**AS-ADJ** Height with solenoid:3¼"

### SOLENOID ADAPTER

ACCU SYNC VALVE RECOMMENDED FLOW RANGE		
Valve	<b>Flow</b> GPM	
PGV-100/101	5 to 40	
PGV-151	20 to 120	
PGV-201	40 to 150	
ICV-101	5 to 40	
ICV-151	20 to 150	
ICV-201	40 to 200	
ICV-301	150 to 300	
IBV-101	5 to 40	
IBV-151	20 to 150	
IBV-201	40 to 200	
IBV-301	150 to 300	

ACCU SYNC APPLICATIONS		
•	Adjustable 20-100 PSI	For full customization, the adjustable Accu Sync can regulate pressure from 20 to 100 PSI
٠	Fixed 30 PSI	Ideal for spray systems
	Fixed 40 PSI	Ideal for Hunter's MP Rotator and large in-line drip systems
	Fixed 50 PSI	Ideal for mid-range rotors
	Fixed 70 PSI	Ideal for larger rotors

### **FIXED**





AS-40

**AS-30** Height with solenoid: 3¼"





AS-50 Height with solenoid: 3¼"

AS-70 Height with solenoid: 31/4"

Height with solenoid: 31/4"





Installation Accu Sync shown installed on ICV and PGV valves.