



Crick, Northampton NN6 7XS
01788 823811
sales@access-irrigation.co.uk
www.access-irrigation.co.uk



Approximate Dimensions: 140cm long, 110cm tall, 103cm wide, 188 kg

Operating off a pumped water supply, this machine offers an excellent cost effective watering option.

The Speedy Rain 40/130 is the ideal solution for watering the following:

- Football, Rugby and Cricket Clubs (Sports Grounds)
- Small scale sports turf
- Landscape/Amenity areas
- Large gardens
- Equestrian/Riding arenas

Features

- Reliable and cost effective irrigation
- Minimum recommended pressure: 4.4 bar
- Low pressure bypass turbine drive
- Low maintenance drive mechanism
- Variable rewind speeds
- Supplied with part/full circle sprinkler mounted on a 2-wheel adjustable width trolley, 4m flexible connection hose with 50mm "Bauer" coupler and mechanical shut-down valve
- Hose guide mechanism

Specifications	
Hose diameter & length	40mm x 130m
Drive mechanism	Turbine
Output range	2.94-7.44m ³ /hr
Throw diameter	26.4-44m
Water application range	2.8-19.9mm
Rewind speed	10-40 meters per hour

Speedy Rain 40/130 Reel Irrigator

RM Speedy Rain 405

PET Hose 40mm x 130 metres

Pressure		Flow Capacity			Irrigated Strip		Rewinding Speed (metres per hour)						
Nozzle	Machine Inlet (after turbine)	Sprinkler			Throw Radius	Throw Diameter	Suggested						
	bar	bar	ltr/sec	m3/hr	mtr	mtr		10	15	20	25	30	40
mm	bar	bar					85%	14.0	9.3	7.0	5.6	4.7	3.5
NOTES													
Water Application (mm)													
8	2.4	1.5	0.82	2.94	15.5	31	26.4	11.2	7.4	5.6	4.5	3.7	2.8
	3	2	0.95	3.42	17	34	28.9	11.8	7.9	5.9	4.7	3.9	3.0
	5.5	4	1.33	4.8	20.5	41	34.9	13.8	9.2	6.9	5.5	4.6	3.4
10	2.9	1.5	1.27	4.56	17	34	28.9	15.8	10.5	7.9	6.3	5.3	3.9
	3.7	2	1.47	5.28	18	36	30.6	17.3	11.5	8.6	6.9	5.8	4.3
	6.6	4	2.07	7.44	22	44	37.4	19.9	13.3	9.9	8.0	6.6	5.0

NOTE

- The pressure at the machine inlet (before turbine) should be at least 2.0 bar higher than the figure given above. I.e. with 10mm nozzle for 3.7 bar pressure after turbine you would need an inlet pressure before the turbine of 5.7 bar. We recommend an inlet pressure (after turbine) of between 4 and 4.5 bar. Also, the faster the rewind speed of the hose the more pressure will be lost over the turbine.
- Maximum pressure at hydrant: 8 bar

These figures are for guidance only